

S-19A



▶ FEATURES

- Smart exterior with exceptional strength
- Foldable small footprint stand
- NeoV Optical Filter™
- Dual digital and analog inputs
- Crisp 700 contrast ratio
- Super wide viewing angle technology
- Auto-adjustment for optimal setting
- Easy-to-use OSD
- Kensington® security slot
- VESA standard wall or arm mount



▶ SPECIFICATION

| | | |
|---------------------|-----------------------------|---|
| Panel | Panel Type | TFT LCD |
| | Panel Size | 19.0" (483mm) |
| | Max. Resolution | SXGA 1280 x 1024 |
| | Pixel Pitch | 0.294mm |
| | Brightness | 300cd/m ² (Typical) |
| | Contrast Ratio | 700:1 (Typical) |
| | Surface Treatments | Hard Coating (2H), Anti-glare Treatment |
| | Viewing Angle (H/V) | 170°/170° (Minimum) |
| | Uni-Directional | 160° (Typical) |
| | Display Color | 16.7M |
| | Response Time (R/F) | 15ms/10ms (Typical) |
| | Frequency (H/V) | H: 24kHz - 80kHz V: 50kHz - 75kHz |
| | Max. Pixel Clock | 135MHz |
| | Life Time | 50,000hrs (Typical) |
| Input | Analog | 15-Pin D-Sub |
| | Digital (DVI-D) | 29-Pin DVI |
| Connector | Power | 3-Pin AC Plug |
| NeoV Optical Filter | Thickness | 3.0mm (0.18") |
| | Reflection Rate | <1% |
| | Transmission Rate | >96% |
| | Hardness | >6H (MOH's Rating) |
| Tilt | Tilt | +5° ~ +25° |
| Mounting | VESA FPMPI | Yes (100mm) |
| Regulation Approval | Safety & EMI | UL/CUL, TUV/BAURT, NORDIC, CB, ISO 13406-2, TCO 95, FCC, CE, BSMI, GOST, VCCI |
| | | VESA |
| Power | Power AC Consumption | 100 - 240V, 50 - 60Hz |
| | | <55W (On) |
| | | <5W (Stand-by) <5W (Off) |
| Dimensions | Net (W x H x D) | 436 x 426 x 200mm (17.2" x 16.8" x 7.9") |
| | Packing (W x H x D) | 550 x 576 x 220mm (21.7" x 22.7" x 8.7") |
| Weight | Net Weight | 8.7Kg (19.2lbs) |
| | Gross Weight | 11.5Kg (25.4lbs) |
| Packing | 1 Pallet | 24 Cartons |
| | 20' Container | 288 Sets |
| | 40' Container | 624 Sets |

* All specifications are subject to change without prior notice.